



# ACE- M | MINI STATIC WHITE INDOOR



LISTED


PROJECT: \_\_\_\_\_

DISTRIBUTOR: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

TYPE \_\_\_\_\_

COMMENTS \_\_\_\_\_



## PHYSICAL

DIMENSIONS	5mm (0.20") WIDTH *2mm (0.08") HEIGHT
OPERATING TEMPERATURE	-40°F (-40°C) TO 131°F (55°C)
IP RATING	IP20
MOUNTING	3M VHB TAPE OR PROFILE
LEAD TYPE	PRESOLDERED 6FT LEAD
PROFILE COMPATIBILITY	MINI PROFILES ONLY
BEAM ANGLE	120°

## ORDERING INFORMATION

PRODUCT	INTENSITY	CCT	IP20	LENGTH
ACE-M	XXX	XXK	IP20	XXFT
ACE M SERIES	200 = 200LM/FT 400 = 400LM/FT	27K = 2700K 30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	IP20 = INDOOR	PROVIDE LENGTH

# ACE- M | MINI STATIC WHITE INDOOR



## ELECTRICAL

OUTPUT	CCT (CORRELATED COLOR TEMPERATURE)					MAX RUN	WATTAGE	LM/ WATT	CUT INTERVALS	INPUT VOLTAGE
	2700K	3000K	3500K	4000K	5000k					
~200 LM/FT	190	198	209	214	217	40'	1.8w/FT	110	50mm (1.97")	24v DC
~400 LM/FT	391	400	413	420	423	30'	3.1w/FT	129		

## PERFORMANCE

CRI	90+
LUMEN MAINTENANCE	50,000
BINNING	SINGLE
WARRANTY	5 YEARS

## ACCESSORIES (SOLD SEPARATELY)

AA-T-2W-LEAD-1FT

2 WIRE ADDITIONAL 1FT LEADER CABLE FOR LEADS LONGER THAN 6FT