

ACE-N-V | NEON VERTICAL STATIC COLOR




PROJECT: _____

DISTRIBUTOR: _____

CONTRACTOR: _____

TYPE _____

COMMENTS _____



PHYSICAL

DIMENSIONS	16mm (0.63") WIDTH *15mm (0.59") HEIGHT
MINIMUM BENDING RADIUS	200mm (7.87")
BEND	VERTICAL BENDING
OPERATING TEMPERATURE	-40°F (-40°C) TO 113°F (45°C)
IP RATING	IP67
MOUNTING	CLIPS OR PROFILE
LEAD TYPE	LEAD SOLD SEPARATELY

ORDERING INFORMATION


PRODUCT	INTENSITY	FEED	CCT	IP	LENGTH
ACE-N-V	XX	XX	X	IP67	XXFT
ACE NEON VERTICAL	SC = STATIC COLOR	EF = END FEED BF = BOTTOM FEED SLF = SIDE LEFT FEED SRF = SIDE RIGHT FEED	R = RED G = GREEN B = BLUE	IP67 = OUTDOOR	1FT = 1 FOOT 4FT = 4 FEET 8FT = 8 FEET 12FT = 12 FEET

ACE-N-V | NEON VERTICAL STATIC COLOR


ELECTRICAL

OUTPUT	COLOR (NANOMETERS)			MAX RUN	PRODUCTION INTERVALS	WATTAGE	INPUT VOLTAGE
	RED	GREEN	BLUE				
SC	620NM	515NM	460NM	30'	50mm (1.97")	3.0w/FT	24v DC


FEED OPTIONS




END FEED



SIDE LEFT FEED



SIDE RIGHT FEED



BOTTOM FEED

PERFORMANCE

LUMEN MAINTENANCE

50,000

WARRANTY

5 YEARS

ACCESSORIES (SOLD SEPARATELY)

AA-N-2W-LEAD-6FT	2 WIRE 6FT IP68 LEADER CABLE (MRI SAFE)
AA-N-2W-LEAD-10FT	2 WIRE 10FT IP68 LEADER CABLE (MRI SAFE)
AA-N-2W-LEAD-30FT	2 WIRE 30FT IP68 LEADER CABLE (MRI SAFE)
AA-N-2W-LEAD-50FT	2 WIRE 50FT IP68 LEADER CABLE (MRI SAFE)
AA-N-2W-JUMP-1FT	2 WIRE 1FT IP68 JUMPER CABLE (MRI SAFE)
AA-N-2W-JUMP-4FT	2 WIRE 4FT IP68 JUMPER CABLE (MRI SAFE)
AA-N-MC	SINGLE NEON MOUNTING CLIP (NOT MRI SAFE)
AA-N-FLEX-PRO-3.28FT	3.28FT STAINLESS STEEL SERRATED FLEXIBLE PROFILE (NOT MRI SAFE)
AA-N-PRO-4FT	4FT ALUMINUM NEON PROFILE (MRI SAFE)
AA-N-V-HYBRID-PRO-3.28FT	3.28FT SEMI RIGID SERRATED VERTICAL BENDING PROFILE (MRI SAFE)
AA-N-2W-EC	2 WIRE SINGLE END CAP (MRI SAFE)