



ACE-S | CORNER BENDING INDOOR



ADHESIVE LISTED


PROJECT: _____

DISTRIBUTOR: _____

CONTRACTOR: _____

TYPE _____

COMMENTS _____



PHYSICAL

DIMENSIONS	6mm (0.24") WIDTH *2mm (0.08") HEIGHT
OPERATING TEMPERATURE	-4°F (-20°C) TO 113°F (45°C)
IP RATING	IP20
MOUNTING	3M VHB TAPE
LEAD TYPE	PRESOLDERED 6FT LEAD
BEAM ANGLE	120°

ORDERING INFORMATION

PRODUCT	INTENSITY	CCT	IP20	LENGTH
ACE-S	XXX	XXK	IP20	XXFT
ACE S SERIES	350 = 350LM/FT 550 = 550LM/FT	27K = 2700K 30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	IP20 = INDOOR	PROVIDE LENGTH

ACE- S | CORNER BENDING INDOOR


ELECTRICAL

OUTPUT	CCT (CORRELATED COLOR TEMPERATURE)					MAX RUN	WATTAGE	LM/ WATT	CUT INTERVALS	INPUT VOLTAGE
	2700K	3000K	3500K	4000K	5000K					
~350 LM/FT	331	339	350	354	353	30'	3.17w/FT	106	50mm (1.97")	24v DC
~550 LM/FT	549	553	550	557	552	20'	4.57w/FT	121		

PERFORMANCE

CRI	90+
LUMEN MAINTENANCE	50,000
BINNING	SINGLE
WARRANTY	5 YEARS

ACCESSORIES (SOLD SEPARATELY)



AA-T-2W-LEAD-1FT

ADDITIONAL 1FT 20AWG 2 WIRE LEADER CABLE
FOR LEADS LONGER THAN 6FT