

ACE-W | W STATIC WHITE OUTDOOR



ADHESIVE LISTED


PROJECT: _____

DISTRIBUTOR: _____

CONTRACTOR: _____

TYPE _____

COMMENTS _____



PHYSICAL

DIMENSIONS	18.55mm (0.73") WIDTH * 9.5mm (0.38") HEIGHT
OPERATING TEMPERATURE	-13°F (-25°C) TO 113°F (45°C)
IP RATING	IP67
MOUNTING	CLIPS OR PROFILE
LEAD TYPE	PRESOLDERED 6FT LEAD
PROFILE COMPATIBILITY	ONLY WITH THE CLIPS AND PROFILE SHOWN IN THIS SPEC SHEET
BEAM ANGLE	30°, 45°, 60°, 20°X45°

ORDERING INFORMATION

PRODUCT	INTENSITY	CCT	OPTIC	IP20	LENGTH
ACE-W	580	XXK	XXXX	IP67	XXFT
ACE W SERIES	580 = 580LM/FT	27K = 2700K 30K = 3000K 35K = 3500K 40K = 4000K	30 = 30° 45 = 45° 60 = 60° 2045 = 20°X45°	IP67 = OUTDOOR	PROVIDE LENGTH

ACE-W | W STATIC WHITE OUTDOOR

ELECTRICAL

OUTPUT	CCT (CORRELATED COLOR TEMPERATURE)				MAX RUN	WATTAGE	LM/ WATT	CUT INTERVALS	INPUT VOLTAGE
	2700K	3000K	3500K	4000K					
~580 LM/FT	564	583	619	660	17'	5.49w/FT	106	125mm (4.92")	24v DC

PERFORMANCE

CRI	90+
LUMEN MAINTENANCE	50,000
BINNING	SINGLE
WARRANTY	5 YEARS

ACCESSORIES (SOLD SEPARATELY)

AA-T-2W-LEAD-1FT	ADDITIONAL 2 WIRE IP67 LEADER CABLE
AA-W-MC	SINGLE MOUNTING CLIP
AA-W-PRO-4FT	4FT ALUMINUM PROFILE WITHOUT LENS
AA-W-PVT	PAIR OF PIVOT CLIPS