

ACE-J-SW-IP67



Job name:
Distributor:
Contractor:
Specifier:
Type:

TECHNICAL DATA	
Dimensions of IP67 tape	0.49" Width * 0.16" Height
Minimum bending radius	2.36"
Bend orientation	Vertical
Flexible	Yes
Operating temperature	-40°F to 131°F
IP Rating	IP67 Outdoor
Lumens available	200, 400, 600, 800
Static white options	1800K, 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, 5000K
Mounting included	3M VHB
Mounting available but sold separately	clips & profiles
Power Lead	Pre-soldered 6' lead
CRI	90+
Warranty	5 years
Input voltage	24V DC
Diodes per ft	43
Field cuttable	Yes every 1.97"
Beam Angle	120°
Dimming	0-10V, ELV
L70	54,000+
Binning	Single




ACE-J-SW-IP67



ELECTRICAL										
OUTPUT W	CCT								MAX CONT. RUN	TOTAL LOAD W/ 96W
	1800K	2200K	2400K	2700K	3000K	3500K	4000K	5000K		
~200LM/FT 1.8W	160LM/FT	175LM/FT	210LM/FT	236LM/FT	237LM/FT	256LM/FT	259LM/FT	259LM/FT	40'	53'
~400LM/FT 3.1W	294LM/FT	301LM/FT	354LM/FT	395LM/FT	407LM/FT	424LM/FT	431LM/FT	431LM/FT	30'	30'
~600LM/FT 4.9W	495LM/FT	506LM/FT	596LM/FT	664LM/FT	685LM/FT	692LM/FT	635LM/FT	635LM/FT	19'	19'
~800LM/FT 6.7W	615LM/FT	639LM/FT	752LM/FT	838LM/FT	864LM/FT	905LM/FT	899LM/FT	897LM/FT	14'	14'

DIMENSIONS



PART BUILDER

Select Product		Select Lumens		Select CCT		Select IP Rating		Select Length
ACE J SERIES	-	200 = 200LM/FT	-	18K = 1800K	-	IP67	-	XXFT
		400 = 400LM/FT		22K = 2200K				
		600 = 600LM/FT		24K = 2400K				
		800 = 800LM/FT		27K = 2700K				
				30K = 3000K				
				35K = 3500K				
				40K = 4000K				
				50K = 5000K				

FINALIZED PART NUMBER

ACE-J - X00 - XXK - IP67 - XXFT



rev 08/26

© 2026 Ace Illuminations. All rights reserved.
Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249

cont. on 2

ACE-J-SW-IP67



ACCESSORIES (sold separately)

LEADER CABLE:	(connects to tape)
AA-T-2W-LEAD-CL	ACE ACCESSORIES TAPE IP20 PRE-SOLDERED 20AWG 2 WIRE LEADER CABLE CUSTOM LENGTH
JUMPER CABLE:	(connects tape to tape)
AA-T-2W-JUMP-CL	ACE ACCESSORIES TAPE IP20 PRE-SOLDERED 20AWG 2 WIRE JUMPER CABLE CUSTOM LENGTH
POWER SUPPLIES:	(powers the tape)
ACE-PWR-36W	ACE 36W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING
ACE-PWR-96W	ACE 96W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING
ACE-PWR-192W	ACE 192W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING
MOUNTING OPTIONS:	(secure the item onto structure)
AA-T-PC-IP67	ACE ACCESSORIES TAPE IP67 PLASTIC CLIP (1 PER FT IS RECOMMENDED)
PROFILES	PLEASE REFER TO ACE PROFILES

