

ACE-N-M-RGBW-IP67



Job name:
Distributor:
Contractor:
Type:

TECHNICAL DATA	
Dimension for Static White	0.39" WIDTH * 0.37" HEIGHT
Minimum bending radius	1.18"
Bend orientation	Vertical
Operating temperature	-4°F to 104°F
IP Rating	IP67 Outdoor
Lumen maintenance (L70)	50,000 hrs
Neon Lead	Sold separately (see below for lengths available)
Lumens available for THE	30 LM/FT
Static White Options	RGB3000K
Mounting available but sold separately	mounting clips or profiles
CRI	90+
Warranty	5 years
Input voltage	24V DC
Diodes per 1.25FT	84
Field cuttable	No
Production intervals	every 2.19"
Beam Angles for Static White	140°
Dimming	DMX
Silicone finish	White
Material	Silicone





ACE-N-M-RGBW-IP67



ELECTRICAL						
WATTAGE	CCT				MAX CONT. RUN PER POWER FEED	TOTAL LOAD W/ 96W DRIVER
	RED	GREEN	BLUE	3000K		
4.3 W/FT	390LM/FT	400LM/FT	412LM/FT	30LM/FT	16'	20'

DIMENSIONS



PART BUILDER

Select Product		Select Lumens		Select Feed		Select CCT		Select IP		Select Length
ACE NEON MINI	-	30 = 30LM/FT	-	EF = END FEED	-	RGB30K = RGB 3000K	-	IP67	-	CLXX = CUSTOM LENGTH

FINALIZED PART NUMBER										
ACE-N-M	-	30	-	EF	-	RGB30K	-	IP67	-	CLXX



ACE-N-M-RGBW-IP67



ACCESSORIES (sold separately)

LEADER CABLE: (connects to neon)

AA-N-M-5W-LEAD-10FT ACE ACCESSORIES IP67 NEON MINI SINGLE 5 WIRE 10FT BARE LEAD



JUMPER CABLE: (connects to neon to neon)

AA-N-M-5W-JUMP-1FT ACE ACCESSORIES IP67 NEON MINI SINGLE 5 WIRE 1FT JUMPER CABLE



AA-N-M-5W-JUMP-6IN ACE ACCESSORIES IP67 NEON MINI SINGLE 5 WIRE 6IN JUMPER CABLE

END CAP: (to terminate the end of a run)

AA-N-M-5W-EC ACE ACCESSORIES IP67 NEON MINI SINGLE 5 WIRE END CAP



MOUNTING: (secure the item onto structure)

AA-N-M-MC ACE ACCESSORIES IP67 NEON MINI SINGLE MOUNTING CLIP



AA-N-M-PRO-4FT ACE ACCESSORIES NEON MINI 4FT PROFILE



DECODER: (bridge the gap between LED strip and controller)

ACE-PWR-DMX-4C ACE 100W 512 DMX DECODER 4 CHANNEL



ACE-PWR-DMX-4C-IP67 ACE 100W 512 DMX DECODER 4 CHANNEL IP67



DECODER/CONTROLLED HYBRID:

ACE-PWR-DMX-4C-BT ACE 100W 512 DMX DECODER 4 CHANNEL BLUETOOTH - DOWNLOAD CASAMBI APP TO CONTROL



rev 08/26

© 2026 Ace Illuminations. All rights reserved.

Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249

cont. on 3

ACE-N-M-RGBW-IP67



ACCESSORIES (sold separately)

CONTROLLER: (instructs the decoder on how the light should perform)

ACE-DMX-CTRL-3S WALL MOUNT THREE SCENE, ONE UNIVERSE, DMX CONTROLLER



ACE-DMX-CTRL-3Z WALL MOUNT THREE ZONE, ONE UNIVERSE, DMX CONTROLLER



ACE-DMX-CTRL-1 WALL MOUNT ONE ZONE, TWO UNIVERSE, DMX CONTROLLER



ACE-DMX-CTRL-10 WALL MOUNT 10 ZONE, ONE UNIVERSE, DMX CONTROLLER




POWER SUPPLIES: (to power the neon)

ACE-PWR-36W ACE 36W CLASS 2 INDOOR & OUTDOOR POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING



ACE-PWR-96W ACE 96W CLASS 2 INDOOR & OUTDOOR POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING



ACE-PWR-192W ACE 192W CLASS 2 INDOOR & OUTDOOR POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING



rev 08/26

© 2026 Ace Illuminations. All rights reserved.

Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249

cont. on 4