

# PRIME-C-SW-IP54



Job name:

Distributor:

Contractor:

Type:

## TECHNICAL DATA

|                                  |                                                                            |
|----------------------------------|----------------------------------------------------------------------------|
| Dimension of single link         | 1.50" Width * 2.00" Height                                                 |
| Operating temperature            | -4°F to 104°F                                                              |
| IP Rating                        | IP54 splash-proof                                                          |
| Mounting                         | rotating mounting plate                                                    |
| Lead not included                | 10FT                                                                       |
| Fixture whip included on fixture | In/out capabilities, 2.13" connection length (fixture to barrel connector) |
| Sizes available                  | 1FT & 4FT                                                                  |
| Lumens available                 | 500LM/FT                                                                   |
| Static white options             | 2700K, 3000K, 3500K, 4000K                                                 |
| Lens options                     | Frosted                                                                    |
| CRI                              | 90+                                                                        |
| Warranty                         | 5 years                                                                    |
| Input voltage                    | 120V-277V                                                                  |
| Plug and play                    | Yes                                                                        |
| Beam Angles for Static White     | 120°                                                                       |
| Dimming                          | 0-10V                                                                      |
| Standard Finish                  | Black                                                                      |
| Finishes available               | White                                                                      |
| Material                         | Aluminum Shell + polycarbonate                                             |



rev 07/26

© 2026 Ace Illuminations. All rights reserved.

Specifications and content subject to change without notice. Protected by international copyright laws.  
info@aceilluminations.com | 702.960.4249


cont. on 1

# PRIME-C-SW-IP54



| ELECTRICAL PER FT |          |          |          |          |                  |                  |                  |
|-------------------|----------|----------|----------|----------|------------------|------------------|------------------|
| OUTPUT   W        | CCT      |          |          |          | MAX RUN<br>@120V | MAX RUN<br>@220V | MAX RUN<br>@277V |
|                   | 2700K    | 3000K    | 3500K    | 4000K    |                  |                  |                  |
| ~500LM/FT   8W    | 480LM/FT | 509LM/FT | 516LM/FT | 525LM/FT | 60'              |                  |                  |

## DIMENSIONS



## PART BUILDER

| Select Product          | Dimming Selected | Select Wattage | Select Length | Select CCT | Beam angle Selected |
|-------------------------|------------------|----------------|---------------|------------|---------------------|
| PRIME-C =<br>PRIME COVE | 010V = 0-10V     | 8W = 8 Watts   | 1 = 1FT       | 27 = 2700K | 120 = 120°          |
|                         |                  |                | 4 = 4FT       | 30 = 3000K |                     |
|                         |                  |                |               | 35 = 3500K |                     |
|                         |                  |                |               | 40 = 4000K |                     |

| FINALIZED PART NUMBER |   |      |   |    |   |   |   |    |   |     |
|-----------------------|---|------|---|----|---|---|---|----|---|-----|
| PRIME-C               | - | 010V | - | 8W | - | X | - | XX | - | 120 |



rev 07/26

© 2026 Ace Illuminations. All rights reserved.

Specifications and content subject to change without notice. Protected by international copyright laws.  
info@aceilluminations.com | 702.960.4249

cont. on 2

# PRIME-C-SW-IP54



## ACCESSORIES (sold separately)

### LEADER CABLE:

(connect to prime cove)

#### PRIME-AA-5W-LEAD-10FT

ACE ACCESSORIES 10 FOOT 5W LEADER CABLE FEMALE BARREL CONNECTOR TO BARE WIRE



### JUMPER CABLE:

(connect prime cove to prime cove)

#### PRIME-AA-5W-JUMP-1FT

ACE ACCESSORIES 1 FOOT 5W JUMPER CABLE FEMALE BARREL CONNECTOR TO BARE WIRE



#### PRIME-AA-5W-JUMP-5FT

ACE ACCESSORIES 4 FOOT 5W JUMPER CABLE FEMALE BARREL CONNECTOR TO BARE WIRE



#### PRIME-AA-5W-JUMP-15FT

### END CAP:

(to terminate the end of a run)

#### PRIME-AA-5W-EC

ACE ACCESSORIES SINGLE 5W MALE END CAP



rev 07/26

© 2026 Ace Illuminations. All rights reserved.

Specifications and content subject to change without notice. Protected by international copyright laws.  
info@aceilluminations.com | 702.960.4249

cont. on 3