

ACE-D-TW-IP20



Job name:

Distributor:

Contractor:

Specifier:

Type:

TECHNICAL DATA

Dimensions of IP20 tape	0.39" Width * 0.08" Height
Minimum bending radius	2.36"
Bend orientation	Vertical
Flexible	Yes
Operating temperature	-4°F to 122°F
IP Rating	IP20 Indoor
Lumens available	700LM/FT
Tunable white options	2700K-6000K
Mounting included	3M VHB
Mounting available but sold separately	clips or profiles
Power Lead	Pre-soldered 6' lead
CRI	90+
R9	90+
Warranty	5 years
Input voltage	24V DC
Diodes per ft	36
Field cuttable	Yes every 3.94"
Beam Angle	120°
Dimming	0-10V, ELV
L70	50,000+
Binning	Single



rev 10/26

© 2026 Ace Illuminations. All rights reserved.

Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249


cont. on 1

ACE-D-TW-IP20



ELECTRICAL			
OUTPUT WATTAGE	CCT	MAX CONT. RUN	TOTAL LOAD W/ 96W
	2700K-6500K		
~700 LM/FT 7.32W/FT	699LM/FT	13'	13'

DIMENSIONS



PART BUILDER

Select Product		Select Lumens		Select CCT		Select IP Rating		Select Length
ACE-D	-	700 = 700LM/FT	-	2765 = 2700K-6500K	-	IP20	-	XXFT

FINALIZED PART NUMBER							
ACE-D	-	700	-	2765	-	IP20	- XXFT



ACE-D-TW-IP20



ACCESSORIES (sold separately)

LEADER CABLE:	(connects to tape)
AA-T-3W-LEAD-CL	ACE ACCESSORIES TAPE IP20 PRE-SOLDERED 20AWG 3 WIRE LEADER CABLE CUSTOM LENGTH
JUMPER CABLE:	(connects tape to tape)
AA-T-3W-JUMP-CL	ACE ACCESSORIES TAPE IP20 PRE-SOLDERED 20AWG 3 WIRE JUMPER CABLE CUSTOM LENGTH
POWER SUPPLIES:	(powers the tape)
ACE-PWR-36W	ACE 36W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING
ACE-PWR-96W	ACE 96W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING
ACE-PWR-192W	ACE 192W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING
MOUNTING OPTIONS:	(secure the item onto structure)
PROFILES	PLEASE REFER TO ACE PROFILES

