

# ACE-D-TW-IP67



Job name:

Distributor:

Contractor:

Specifier:

Type:

## TECHNICAL DATA

|                                        |                            |
|----------------------------------------|----------------------------|
| Dimensions of IP67 tape                | 0.49" Width * 0.16" Height |
| Minimum bending radius                 | 2.36"                      |
| Bend orientation                       | Vertical                   |
| Flexible                               | Yes                        |
| Operating temperature                  | -4°F to 122°F              |
| IP Rating                              | IP67 Outdoor               |
| Lumens available                       | 700LM/FT                   |
| Tunable white options                  | 2700K-6000K                |
| Mounting included                      | 3M VHB                     |
| Mounting available but sold separately | clips or profiles          |
| Power Lead                             | Pre-soldered 6' lead       |
| CRI                                    | 90+                        |
| R9                                     | 90+                        |
| Warranty                               | 5 years                    |
| Input voltage                          | 24V DC                     |
| Diodes per ft                          | 36                         |
| Field cuttable                         | Yes every 3.94"            |
| Beam Angle                             | 120°                       |
| Dimming                                | 0-10V, ELV                 |
| L70                                    | 50,000+                    |
| Binning                                | Single                     |



rev 01/26

© 2026 Ace Illuminations. All rights reserved.

Specifications and content subject to change without notice. Protected by international copyright laws.  
info@aceilluminations.com | 702.960.4249


cont. on 1

# ACE-D-TW-IP67



| ELECTRICAL            |             |               |                   |
|-----------------------|-------------|---------------|-------------------|
| OUTPUT   WATTAGE      | CCT         | MAX CONT. RUN | TOTAL LOAD W/ 96W |
|                       | 2700K-6500K |               |                   |
| ~700 LM/FT   7.32W/FT | 699LM/FT    | 13'           | 13'               |

## DIMENSIONS



## PART BUILDER

| Select Product |   | Select Lumens  |   | Select CCT         |   | Select IP Rating |   | Select Length |
|----------------|---|----------------|---|--------------------|---|------------------|---|---------------|
| ACE-D          | - | 700 = 700LM/FT | - | 2765 = 2700K-6500K | - | IP67             | - | XXFT          |

| FINALIZED PART NUMBER |   |     |   |      |   |      |        |
|-----------------------|---|-----|---|------|---|------|--------|
| ACE-D                 | - | 700 | - | 2765 | - | IP67 | - XXFT |



# ACE-D-TW-IP67



## ACCESSORIES (sold separately)

|                   |                                                                                       |
|-------------------|---------------------------------------------------------------------------------------|
| LEADER CABLE:     | (connects to tape)                                                                    |
| AA-T-3W-LEAD-CL   | ACE ACCESSORIES TAPE <b>IP20</b> PRE-SOLDERED 20AWG 3 WIRE LEADER CABLE CUSTOM LENGTH |
| JUMPER CABLE:     | (connects tape to tape)                                                               |
| AA-T-3W-JUMP-CL   | ACE ACCESSORIES TAPE <b>IP20</b> PRE-SOLDERED 20AWG 3 WIRE JUMPER CABLE CUSTOM LENGTH |
| POWER SUPPLIES:   | (powers the tape)                                                                     |
| ACE-PWR-36W       | ACE 36W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING                          |
| ACE-PWR-96W       | ACE 96W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING                          |
| ACE-PWR-192W      | ACE 192W CLASS 2 POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING                         |
| MOUNTING OPTIONS: | (secure the item onto structure)                                                      |
| PROFILES          | PLEASE REFER TO ACE <a href="#">PROFILES</a>                                          |

