ACE-NH1-TW-IP67

Job name:	
Distributor:	
Contractor:	
Type:	

	TECHNICAL DATA
Dimension for TW	0.63" WIDTH * 0.67" HEIGHT
Minimum bending radius	7.87"
Bend orientation	Horizontal bending
Operating temperature	-13°F to 140°F
IP Rating	IP67 Outdoor
Lumen maintenance (L70)	50,000 hrs
Neon Lead	Sold separately (see below for lengths available)
Lumens available for Tunable White	250LM/FT
Tunable White Options	2700K-6500K
Mounting available but sold separately	mounting clips or profiles
CRI	90+
Warranty	5 years
Input voltage	24V DC
Binning	Single
Field cuttable	No
Production intervals	every 2.81"
Beam Angles for TW	120°
Dimming	DMX
Silicone finish	White
Material	Silicone


rev 10/26
© 2026 Ace Illuminations. All rights reserved.
Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249


cont. on 1

ACE-NH1-TW-IP67


ELECTRICAL			
OUTPUT	WATTS	CCT	MAX CONT. RUN PER POWER FEED	TOTAL LOAD W/ 96W DRIVER
~250LM/FT	3.4W/FT	240LM/FT	16′	28′

DIMENSIONS








MALE CONNECTOR



FEMALE CONNECTOR







PART BUILDER

Select Product		Select Lumens		Select Feed		Select CCT		Select IP		Select Length
ACE NEON HORIZONTAL 1	-	250 = 250LM/FT	-	EF = END FEED BF = BOTTOM FEED SLF = SIDE LEFT FEED SRF = SIDE RIGHT FEED	-	TW = 2700K - 6500K	-	IP67	-	CLXX = CUSTOM LENGTH

FINALIZED PART NUMBER										
ACE-NH1	-	250	-	XX	-	TW	-	IP67	-	CLXX


rev 10/26
© 2026 Ace Illuminations. All rights reserved.
Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249


cont. on 2


ACE-NH1-TW-IP67


ACCESSORIES (sold separately)

LEADER CABLE:	(connects to neon)
AA-N1-3W-LEAD-10FT	ACE ACCESSORIES IP67 NEON 1 SERIES SINGLE 3 WIRE 10FT BARE LEAD
AA-N1-3W-LEAD-30FT	ACE ACCESSORIES IP67 NEON 1 SERIES SINGLE 3 WIRE 30FT BARE LEAD
AA-N1-3W-LEAD-50FT	ACE ACCESSORIES IP67 NEON 1 SERIES SINGLE 3 WIRE 50FT BARE LEAD
JUMPER CABLE:	(connects to neon to neon)
AA-N1-3W-JUMP-1FT	ACE ACCESSORIES IP67 NEON 1 SERIES SINGLE 3 WIRE 1FT JUMPER CABLE
AA-N1-3W-JUMP-4FT	ACE ACCESSORIES IP67 NEON 1 SERIES SINGLE 3 WIRE 4FT JUMPER CABLE
END CAP:	(to terminate the end of a run)
AA-N1-3W-EC	ACE ACCESSORIES IP67 NEON 1 SERIES SINGLE 3 WIRE END CAP
MOUNTING:	(secure the item onto structure)
AA-N1-M-MC	ACE ACCESSORIES NEON 1 SERIES IP67I SINGLE MOUNTING CLIP
AA-N1-PRO-4FT	ACE ACCESSORIES NEON 1 SERIES 4FT PROFILE
AA-N1-PRO-FLEX-DW-4FT	ACE ACCESSORIES NEON 1 SERIES 4FT PROFILE FLEXIBLE MUD-IN DRYWALL
AA-N1-PRO-RC-4FT	ACE ACCESSORIES NEON 1 SERIES 4FT PROFILE RECESSED









rev 10/26

© 2026 Ace Illuminations. All rights reserved.
Specifications and content subject to change without notice. Protected by international copyright laws.

info@aceilluminations.com | 702.960.4249

cont. on 3

ACE-NH1-TW-IP67

ACCESSORIES (sold separately)

AA-N1-PRO-FLEX-4FT	ACE ACCESSORIES NEON 1 SERIES 4FT STAINLESS STEEL SERRATED FLEXIBLE PROFILE	
AA-NH1-PRO-HYBRID-4FT	ACE ACCESSORIES IP67 NEON 1 SERIES 4FT HYBRID NEON	
AA-N1- PRO-RW-4FT	ACE ACCESSORIES IP67 NEON 1 SERIES 4FT RACEWAY PROFILE	

DECODER:	(bridge the gap between neon and controller)	
ACE-PWR-DMX-4C	ACE 100W 512 DMX DECODER 4 CHANNEL	
ACE-PWR-DMX-4C-IP67	ACE 100W 512 DMX DECODER 4 CHANNEL IP67	


CONTROLLER:	(instructs the decoder on how the light should perform)	
ACE-DMX-CTRL-3S	WALL MOUNT THREE SCENE, ONE UNIVERSE, DMX CONTROLLER	
ACE-DMX-CTRL-3Z	WALL MOUNT THREE ZONE, ONE UNIVERSE, DMX CONTROLLER	
ACE-DMX-CTRL-1	WALL MOUNT ONE ZONE, TWO UNIVERSE, DMX CONTROLLER	
ACE-DMX-CTRL-10	WALL MOUNT 10 ZONE, ONE UNIVERSE, DMX CONTROLLER	

rev 10/26
© 2026 Ace Illuminations. All rights reserved.
Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249

cont. on 4

ACE-NH1-TW-IP67

ACCESSORIES (sold separately)

POWER SUPPLIES:	(to power the basilisk)	
ACE-PWR-36W	ACE 36W CLASS 2 INDOOR & OUTDOOR POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING	
ACE-PWR-96W	ACE 96W CLASS 2 INDOOR & OUTDOOR POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING	
ACE-PWR-192W	ACE 192W CLASS 2 INDOOR & OUTDOOR POWER SUPPLY 120V-277V INPUT, 5 IN 1 DIMMING	

© 2026 Ace Illuminations. All rights reserved.
Specifications and content subject to change without notice. Protected by international copyright laws.
info@aceilluminations.com | 702.960.4249

cont. on 5